PROFESSIONAL LINE

Honing & Polishing

A3 YELLOW

Wet polishing powder for a vitreous effect Suitable for all lime-based materials, including marble, limestone, travertine, and marble agglomerates.

A3 YELLOW is a high-performing wet polishing powder for all types of marble and lime-based materials, such as limestone, travertine, marble-concrete agglomerates, and marble-resin agglomerates. Its formulation offers excellent results when it comes to the clarity and depth of shine on the finished surface. **A3 YELLOW** does not contain wax but it reacts with the material it is applied to, boosting shine and at the same time, leaving the surface with a lasting resistance to dirt and foot traffic. **A3 YELLOW** is also able to reduce the slipperiness on dry flooring.

BENEFITS

- ✓ Deep vitreus shine
- ✓ Great dirt-resistant protection
- ✓ Great foot-traffic resistance
- ✓ Wax-free formula

USES

This product can be used on both indoor and outdoor surfaces.
Suitable for use on: marble, limestone; travertine; marble-cement agglomerates; marble-resin agglomerates.

COVERAGE

For surface **polishing** 40/50 m^2/kg
For surface **maintenance** 50/100 m^2/kg

APPLICATION EQUIPMENT

Single disc machine with at least 1.5 HP; manual rotary brush.
Faber Chimica is able to supply the WARRIOR Single disc machine, which has a power of 2.2 HP, and is optimised for the correct application of any product.

APPLICATION STEPS

Surface preparation

- Carefully clean the surface, making sure to remove any dust or dirt present.
- We recommend proceeding to apply the product in stages, covering surfaces approximately 2m^2 at a time.
- Never apply **A3 YELLOW** to wet surfaces. **A3 YELLOW** can be used on slightly damp surfaces; therefore, please ensure that the surface to be treated is as dry as possible.
- Apply **A3 YELLOW** to surfaces with a temperature of between +5 and +40°C
- Any adjacent surfaces not being treated with the product must be protected.

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- Pour 1-2 spoons of product onto the surface to be treated.
- Add a sufficient amount of water to the product to create a creamy/fluid paste that is easy to distribute. As a rough guide, each spoonful of product requires around 2 spoons of water.
- As soon as the water has been added to the powder, proceed to apply it to the surface using the single disc machine, fitted with a white pad. Continue with the single disc machine, taking care to cover the whole surface area evenly with the achieved paste. Try to pass over each section of the floor the same number of times.

MADE IN ITALY 100%

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

APPLICATION STEPS

- During the application process, the mix must maintain its creamy consistency and therefore, if it should become too dry, gradually add a little water.
- Continue to buff with the single disc machine until the surface has reached its maximum shine. The shine results are easy to check during application by removing a small area of product using a squeegee mop or similar, and checking the level of shine achieved.
- Once the required shine has been achieved, vacuum or remove any residues from the surface. Pass on to the area of the next surface.

When **polishing after grinding** and to restore shine on particularly worn surfaces, pass over each section at least 20-25 times with the single disc machine.

To **maintain the shine** pass over each section 10-15 times with the single disc machine is sufficient; use a slightly smaller amount of powder, around 1-2 spoonfuls for each section.

Resuming the surface use

After carefully removing any residues and rinsing the surface with water, the floor can be opened for use.

MAINTENANCE PRODUCTS

- For the daily maintenance of a surface treated with **A3 YELLOW**, we recommend: **NEUGEL** or **ALGAFLOOR**
- For heavy-duty cleaning of a surface treated with **A3 YELLOW**, we recommend: **FABER 30**
- To maintain the shine of a surface polished with **A3 YELLOW**, we recommend: **CRISTALFAB** or **CHRISTALFAB WHITE PAD**
- For stain-proof protection of a surface polished with **A3 YELLOW**, we recommend: **HIDRO 150** or **PROTEX WB**

INSTRUCTIONS AND GUIDELINES

- Do not allow the product to dry during the application process. Frequently check consistency and add water as needed to return the product to its fluid/creamy state.
- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces
- Apply the product to surfaces with a temperature of between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

PHYSICAL-TECHNICAL DATA

Formula	Powder
Color	Yellow
Odor	Slightly pungent
pH:	1,5 ± 0,5

MADE IN ITALY

100%

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

STORAGE	Keep the container tightly closed and store in a cool, dry place.
SHELF LIFE	48 months in the original, sealed packaging, stored in a cool, dry place.
PACKAGING	1 kg bucket – 12 buckets per box 5 kg bucket – 4 buckets per box
SAFETY	When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Revisione 5.1 – 17/10/2024

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

MADE IN ITALY
100%

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM